In the Claims:

Kindly amend the claims as follows:

J C WRAY

1. (Currently amended) Insert suitable for being placed in a wall, ceiling or other element, wherein said insert comprises ventilation means and an aperture in which, inside the insert, means for snap-fitting of electrical installation means, such as a lamp socket, connection box, halogen light fitting or the like, are provided, and that furthermore resilient means are provided for fastening of the insert in said wall, ceiling or other element.

wherein the insert is an expansion unit comprising two coaxially arranged cylindrical elements which include at least three zones in axial direction:

a first zone that in the assembled condition will be farthest from the surface on which the item is mounted and at the inner side of which is provided engagement means;

a deformation zone in which there is provided pre-shaped deformation means, whereby the item, when subjected to axial deformation, will expand the cylindrical cross-section compared with the cross-section of the cylinder before the deformation; and

a first spacer zone;

further wherein the inner cylindrical element includes at least two zones:

a first zone in which at the outer side of the cylinder there is provided engagement means corresponding to and intended for engagement against the engagement means of the outer cylinder; and

a second spacer zone.

- 2. (Canceled) without prejudice.
- 3. (Currently amended) Insert The insert according to claim 1, characterised in that the end comprises one or more apertures for letting air in or out of the insert.

- 4. (Currently amended) Insert The insert according to claim 1, characterised in that the ventilation means is a ventilator comprising a fan, and that optionally the current supply to the electrical installation also supplies current to the ventilation means.
- 5. (Currently amended) Insert The insert according to claim 1, characterised in that the side of the end, facing away from the aperture is supplied with distance keeping means, as for example legs, protrusions, netting basket or the like.
- (Currently amended) Insert The insert according to claim 1, characterised in that 6. the insert is provided with means for attaching the electrical installation means, and that further means are provided for allowing the air stream created by the ventilation means to pass the electrical installation means.
- 7. (Currently amended) Insert according to claim 1, characterized in that Insert suitable for being placed in a wall, ceiling or other element, wherein said insert comprises ventilation means and an aperture in which, inside the insert, means for snap-fitting of electrical installation means, are provided, and that furthermore resilient means are provided for fastening of the insert in said wall, ceiling or other element, wherein the resilient means comprises one or more members pivotably mounted in the wall of said insert, where each member has a first section, a middle section, and a second section, where a pin is arranged through said middle section and that said pin is pivotably accommodated in the wall of the insert, such that the resilient means may pivot in relation to the insert, and that in a first position the first section is accommodated in a recess provided in the outer surface of said insert wall, and that said second section is exposed inside the insert, and that in a second position the first section extends out from the wall of the insert, preferably towards the aperture end of the insert, and that said second

section is releasably but firmly engaged in a slit or recess provided on the inner surface of the insert.

- 8. (Currently amended) Insert The insert according to claim § 7, characterised in that the first section comprises a steel blade, preferably spring steel, and that the rest of the pivotably mounted member is made from a polymer, preferably a plastic material complying with 5VA requirements, and that further the pin is made from metal, preferably stainless steel.
 - 9. (New) The insert of claim 8, wherein the steel blade is of spring steel material.
- 10. (New) The insert of claim 8, wherein the polymer is a plastic material complying with 5VA requirements.
 - 11. (New) The insert of claim 8, wherein the metal is stainless steel.
- 12. (New) The insert of claim 7, wherein the electrical installation means is coupled to fixtures selected from the group consisting of lamp sockets, connection boxes, halogen lights, fans, and combinations thereof.
- 13. (New) The insert of claim 1, wherein the electrical installation means is coupled to fixtures selected from the group consisting of lamp sockets, connection boxes, halogen lights, fans, and combinations thereof.
- 14. (New) The insert of claim 4, further comprising a current supply to the electrical installation means.
- 15. (New) The insert of claim 14, wherein the current supply additionally supplies current to the ventilation means.
- 16. (New) The insert of claim 5, wherein the distance keeping means is selected from the group consisting of legs, protrusions, netting basket, and combinations thereof.